



TECHNICAL  
DATA

CORU-ANTIPAS

## *PRODUCT DESCRIPTION*

It is a solvent-based, synthetic alkyd resin-based primer/paint containing zinc phosphate anticorrosive agents. It is a strong protector against rust for iron and other metal surfaces. It is a primer paint with high covering power that can be thinned with synthetic thinner.

---

## *AREAS OF USE*

It is used against rust on all kinds of metal surfaces, iron-steel-sheet metal surfaces.

---

# TECHNICAL SPECIFICATIONS

Connector type	Acrylic resin
Viscosity (Stormer Ku /25°C)	125 +/- 5 Ku
Solid Matter (by weight - %)	70 ± 3
Brightness	Along with
Flash Point (°C)	36
Drying time (20°C)	Touch Dry: 4 - 5 hours Dust-free drying: 7 - 8 hours Full Dry: 24 hours
Cover (Teorik – m <sup>2</sup> /lt)	4.00 – 7.00 m <sup>2</sup> /kg (at 20-30 μ dry film thickness) It may vary depending on the ambient conditions and the absorbency and smoothness of the surface.
Thinning Ratio	10-15% synthetic thinner
Application Tools	Brush, roller, air gun
Recommended Number of Floors	Single floor
Application Terms	+5 - +35°C

# *APPLICATION*

- There should be no rust, dirt, oil or burrs on the application surface.
  - It is applied with a brush, roller or gun.
  - It is recommended to apply two coats.
  - Wait 24 hours between coats.
  - Paint application begins 24 hours after anti-rust application.
- 

# *STORAGE, PACKAGING, CONSUMPTION*

It can be stored for two years in its original packaging in an environment with a temperature of +5 - +35°C, away from direct sunlight.

20 kg tin

---

# *SAFETY AND WARNINGS*

- **H225:** Highly flammable liquid and vapour.
- **H302/312/332:** Harmful if swallowed, in contact with skin and if inhaled.
- **P102:** Keep out of reach of children.
- **P271:** Use only outdoors or in a well-ventilated area.
- **P301 + P310:** IF SWALLOWED, immediately call a POISON CENTER or doctor/physician.
- **P305 + P351 + P338:** IF IN EYES, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- **P381:** Eliminate all ignition sources if safe to do so.
- **P404:** Keep in closed container.
- **P410:** Protect from sunlight.
- **P501:** Dispose of contents/container in accordance with local/regional/national/international regulations.