



TECHNICAL
DATA

CORU OIL PAINT

PRODUCT DESCRIPTION

It is a synthetic resin based, glossy, top coat paint with strong adhesion to the surface, high covering power, non-fading colors, protecting the surface on which it is applied, and a decorative appearance.

AREAS OF USE

It can be used safely for decorative and protective purposes on the surfaces of all kinds of wooden and metal structural elements such as doors, windows, railings on interior and exterior facades, on the surface of marine vehicles and on agricultural equipment.

TECHNICAL SPECIFICATIONS

Connector type	Alkyd resin
Viscosity(Ku /25°C)	120 +/- 5 Ku
Solid matter(by weight - %)	70 ± 3
Brightness	Shiny
Drying(20°C at 60% HR)	Touch dry: 3-4 Dust-free dry: 6-7 hours Complete dry: 24 hours
Coverage(theoretical - kgm2)	10.00 – 12.00 m ² /lt (20-30 μ dry film thickness) May vary depending on ambient conditions, absorbency and smoothness of the surface.
Thinning ratio	%5-10
Thinner	Synthetic thinner
Application tools	Roller, brush, air gun,
Recommended number of floors	Two coats, at least 12 hours should pass between coats
Conditions of application	+5 - +35°C

APPLICATION

Old Wood Surface: Old and swollen paints are scraped off, sanded, and preferably primed with CORUNEX Wood Protector or CORUNEX Synthetic Primer.

New Wood Surface: Knots are burned, preferably primed with CORUNEX VARNISHED Wood Protector or CORUNEX Synthetic Primer.

Old Metal Surface: Old and swollen paints are scraped off, sanded, and primed with CORUNEX Anti-Rust.

New Metal Surface: The surface is cleaned from dirt, dust and oil. It is primed with CORUNEX Anti-Rust.

12 hours after the primer application; CORU-OIL should be applied. It is diluted with 5-10% synthetic thinner and applied to the surface with a brush, roller or paint gun in two layers. 24 hours should be waited between layers.

SAFETY AND WARNINGS

- **H225:** Highly flammable liquid and vapour.
 - **H302/312/332:** Harmful if swallowed, in contact with skin and if inhaled.
 - **P102:** Keep out of reach of children.
 - **P271:** Use only outdoors or in a well-ventilated area.
 - **P301 + P310:** IF SWALLOWED, Immediately call a POISON CENTER or doctor/physician.
 - **P305 + P351 + P338:** IF IN EYES, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - **P381:** Eliminate all ignition sources if safe to do so.
 - **P404:** Keep in closed container.
 - **P410:** Protect from sunlight.
 - **P501:** Dispose of contents/container in accordance with local/regional/national/international regulations.
-

STORAGE, PACKAGING, CONSUMPTION

It can be stored for two years in its original packaging in a dry environment at +5 - +35°C, away from direct sunlight.