

TECHNICAL DATA

CORUPREMIER



PRODUCT DESCRIPTION

It is a highly advanced acrylic-based primer that can penetrate deeply into cement, plaster and lime surfaces on exterior and interior surfaces.

AREAS OF USE

- In exterior and interior spaces, vertical and ceilings
- Plaster, lime whitewash on low quality absorbent surfaces that have lost their properties
- On highly absorbent or dusty surfaces
- It is used on surfaces with high absorbency.

TECHNICAL SPECIFICATIONS

Drying time	60-120 dk
Colour	Transparent
Ph	6-9
Solid matter ratio	%27
Adhesion strength by pull-off	≥1 N/mm ²
Drying time	60-120 dk

FEATURES

- When dry, it gains a transparent appearance, prevents the absorbency of the plaster surface and ensures the integration of the paint with the surface.
 - Thanks to its spreading feature, it penetrates the surface quickly.
 - Provides high economy in paint consumption.
 - It ensures that the paint applied on it preserves its liveliness and color.
 - It integrates with the surface thanks to its high strength.
 - It is resistant to severe climatic conditions.
 - It prevents possible micro cracks that may occur on the surface.
 - It is easy to apply.
 - It prevents rapid water loss in cement and gypsum based plasters.
 - If applied correctly, it will not cause shedding or frizz.
 - It prevents water and moisture permeability to a large extent.
-

SURFACE PREPARATION

- CORUPREMIER 1/7 transparent primer; The surfaces to be applied must be solid, free of loose and weak parts, free of frost, free from foreign substances and other contaminants, clean and dry.
 - After sanding and dusting the surface of plaster and similar surfaces, primer application should be started.
-

APPLICATION

- It is diluted 1/7 with water.
 - CORUPREMIER 1/7 clear primer is applied in a single coat by roller, brush or spray.
 - To ensure deep penetration, it is recommended to apply by saturating the material on the surface.
 - In order to maintain the homogeneity of the primer, it should be mixed at intervals during the work.
 - Paint application can be started at least 5 hours after applying CORUPREMIER 1/7 transparent primer.
 - During application, care must be taken to ensure that the surface and ambient temperature is between a minimum of (+) 5°C and a maximum of (+) 30°C.
-

STORAGE, PACKAGING, CONSUMPTION

- It should be stacked up to 3 times in its original packaging.
- It should be stored in a closed area.
- Necessary precautions must be taken against water, humidity, frost and severe weather conditions.
- It should be stored on a pallet and in a dry place between +10°C and +25°C.
- Punctured, opened and burst buckets should be closed or used immediately.
- If the specified storage conditions are observed, the storage life is 12 months.
- The packaging box in the 15 kg bucket is white and becomes transparent when dry.
- The consumption rate is 0.1 - 0.8 kg/m² depending on the application technique and the absorbency of the surface.
- A controlled sample is recommended for exact consumption.
- The specified rates are theoretical standards and may vary depending on the application method and intensity of use.

SAFETY AND WARNINGS

- The recommended dilution rate should be applied and adhered to.
- It should not be brought into contact with skin, eyes and mouth, and the application should be carried out by taking the necessary work safety precautions.
- Avoid applying at temperatures below +5°C and above +35°C, and do not try to use frozen material by adding water.