



TECHNICAL
DATA

CORU-SHIELD

PRODUCT DESCRIPTION

Surface Reinforcing Primer is a solvent-based, acrylic copolymer resin exterior primer.

AREAS OF USE

Precast Surface Primer can be applied to precast, brick, brute concrete, betopan, putty surfaces, exterior glass fiber reinforced surfaces, cement-based plastered exterior surfaces.

FEATURES

- Thanks to its special formula, it penetrates perfectly into the surfaces on which it is applied and integrates with the surface.
- Provides maximum alkali resistance on surfaces.
- Does not contain lead.

APPLICATION

- Precast Surface Primer can be applied to precast, brick, brute concrete, betopan, putty surfaces, exterior glass fiber reinforced surfaces, cement-based plastered exterior surfaces.
- Precast surface primer must be used before and after putty.
- Until the product is completely dry, the surfaces should be protected from all kinds of rain, dew and frost, and application under abundant breeze and sunlight should be avoided.
- If application is necessary in hot weather, it should not be done between 10:00 and 16:00.
- Shadow facades should be monitored and attention should be paid to the painting process.
- In applications to be made outside the specified temperature values, the facades must be protected from external effects and the desired application conditions must be provided.
- Primer application should be done in a single coat using a brush or roller.
- The application to be made on Precast Surface Primer should be completed with our preferred final coat exterior paints' own primer.
- WARNING-1: During application, make sure that the surface and air temperature is at least between +5°C and +30°C.
- WARNING-2: Due to the structure of the product, it should not be applied on thermal insulation plaster as it may damage the EPS thermal insulation board.

STORAGE, PACKAGING, CONSUMPTION

The product should be stored in accordance with national regulations. Packages should be stored in dry, cool, well-ventilated areas, away from heat and spark sources. Handle with care.

SAFETY AND WARNINGS

- **H225:** Highly flammable liquid and vapour.
- **H302/312/332:** Harmful if swallowed, in contact with skin and if inhaled.
- **P102:** Keep out of reach of children.
- **P271:** Use only outdoors or in a well-ventilated area.
- **P301 + P310:** IF SWALLOWED, Immediately call a POISON CENTER or doctor/physician.
- **P305 + P351 + P338:** IF IN EYES, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- **P381:** Eliminate all ignition sources if safe to do so.
- **P404:** Keep in closed container.
- **P410:** Protect from sunlight.
- **P501:** Dispose of contents/container in accordance with local/regional/national/international regulations.