

CORUNEX

REINFORCING
CONCRETE

www.corunex.com

TECHNICAL DATA

CORU-WAY



PRODUCT DESCRIPTION

It is an alkyd resin-based, solvent-based, chlorinated rubber modified, air drying, surface-
penetrating, easy to apply, abrasion-resistant, fast drying marking paint that can be used
in road and pavement markings.

AREAS OF USE

It can be applied to asphalt and abrasion (rough) concrete surfaces. It was developed for marking
lines on highways, airports, runways, pedestrian crossings, tennis courts, basketball and football
fields.

TECHNICAL SPECIFICATIONS

Connector Type	Alkyd resin
Viscosity (KU)(25°C)	105 ± 5
Solid Matter (by Weight) (%)	68 ± 3
Brightness	Along with
Covering Capacity (Theoretical)	1,50 – 2,50 m/kg
Thinning Ratio	9:5-10
Thinner	Good Line Thinner
Application Temperature	-5 - +30°C

APPLICATION

The surface to be applied must be absolutely dry, oil-free and clean. Smooth and/or low-absorbency surfaces such as helicopter concrete must be roughened before application. It is diluted with 5% thinner, mixed well (preferably with a low-speed mixer) and applied with a roller; in applications to be made by spraying, the dilution rate can be made at 10-15%. If glass beads are to be poured on it, the process should be started immediately after the paint application before the paint dries. It is thinned and applied with a roller.

STORAGE, PACKAGING, CONSUMPTION

It can be stored for two years in its original packaging in an environment with a temperature of +5 - +35°C, away from direct sunlight.

WARNINGS

H225 : Highly flammable liquid and vapour.

H302/312/332 : Harmful if swallowed, in contact with skin and if inhaled.

P102 : Keep out of reach of children.

P201 : Use only outdoors or in a well-ventilated area.

P301 + P310 : IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P305 + P351 + P338 : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P382 : Eliminate all ignition sources if safe to do so.

P404 : Keep in closed container.

P403 : Protect from sunlight.

P505 : Dispose of contents/container in accordance with local/regional/national/international regulations.