

## TECHNICAL DATA

## CORUDILAT BAND Dilation Band



## *PRODUCT DESCRIPTION*

CORUDILAT TAPE is an elastomer reinforced dilation tape used in the insulation of building dilatations, joints of different building materials and side walls.

---

## *AREAS OF USE*

In foundations and curtains,

- In constantly wet areas such as pools,
- In water tanks, treatment plants and tunnels,
- At the ends of terraces, balconies, parapets and roofs,
- In expansion joints of underground floors,
- It is applied for the insulation of cold joints and expansion joints in curtain walls and floors.

## *PRODUCT FEATURES*

It is very soft and easy to apply.

---

## *APPLICATION*

The width of the tape should be greater than the width of the expansion joint. After the expansion joint is fixed to both surfaces, there should be enough excess to give an omega ( $\Omega$ ) shape. The expansion joint holes are pressed onto the surface so that they are on top of the Assembly Putty and some putty is allowed to come out of the holes. There should be no air gaps in between. Finally, enough putty is applied to the tape and the edges to completely cover the holes of the tape. The longitudinal joints are joined by a heat source or special adhesive, overlapping each other by 20 cm. Open flame and epoxy assembly mortar are not used for this process. The tape should not be moved until the epoxy adhesive hardens.

---

## *PACKAGING AND CONSUMPTION*

Length: 25 meters/roll Width: 15,20,25,30 cm

---

## *STORAGE*

Shelf life is unlimited. Rolls should be stored upright.

## *WARNINGS*

For details not found sufficient above, please obtain written information. Otherwise, errors resulting from lack of information do not impose any liability on our company. This technical bulletin invalidates previous bulletins related to this product.