

## TECHNICAL DATA

CORUFAY



### *PRODUCT DESCRIPTION*

It is an acrylic emulsion based primer with high adhesion strength, applied to ceramic before applying ceramic coating to increase adhesion.

### *AREAS OF USE*

It is used on ceramic, glossy, mosaic or wooden surfaces to increase adhesion or reduce the absorbency of the surface.

---

## *PRODUCT FEATURES*

- It is ready to use and can be applied easily and quickly.
- It is odorless and can be used safely indoors.
- It has high adhesion strength.
- Applied before cement and plaster based coatings, it prevents rapid water loss of the mortar.
- It has high resistance to moisture.
- It has high water impermeability thanks to the special polymer it contains.

---

## *APPLICATION*

- The surface to be applied must be solid, free from all dirt, oil, dust and frost, clean and dry.
- The surface must be free of loose and weak parts, cement grout, ponded water, coatings, etc. foreign materials and other contaminants.
- The surface must be cleaned and made suitable with high pressure water or abrasive equipment.
- Mix for at least 3 minutes with a low speed mixer in a clean container or in its own packaging, free of any substances that may prevent adhesion. Do not add foreign substances.
- A single coat is applied to the surface with a brush or roller. It is recommended to make a preliminary trial for different applications. If several coats are to be applied, a minimum of 1 hour should be waited between coats, and a minimum of 3 hours should be waited for the final coat.
- It is not used as a waterproofing material alone.

---

## *PACKAGING AND CONSUMPTION*

- 15 L, 12.5 L, 2.5 L
- For exact consumption, a controlled sample study should be done.

---

## *STORAGE*

- It can be stored for 3 years in its unopened packaging, in a cool and dry place, protected from frost and direct sunlight. Close the lid of the packaging immediately after use in an airtight manner.
- It should be stored in a closed area.
- Necessary precautions must be taken against water, humidity, frost and severe weather conditions.
- - It should be stored on a pallet and in a dry place between (+-) 10°C and (+) 25°C.
- Punctured, opened and burst buckets should be used or closed immediately.
- If the specified storage conditions are observed, the storage life is 12 months.

---

## *THE GUARDIANS*

For details not found sufficient above, please obtain written information. Otherwise, errors resulting from lack of information do not impose any liability on our company. This technical bulletin invalidates previous bulletins related to this product.