

CORUNEX

MEMBRANES
KÖRNYUTÓK

TECHNICAL DATA

MS POLIMER ASTAR
(GLOBAL ASTAR)



PRODUCT DESCRIPTION

MS POLYMER PRIMER: It is an Acrylic Polymer resin based primer that is applied before waterproofing and used without dilution depending on the surface condition.

AREAS OF USE

- On large surface, highly detailed, flat and sloping roofs,
- On drip trays on terraces and balconies,
- It can be easily applied by everyone in the waterproofing of channels and flumes, chimney edges, eaves, gutters and filters,
- It does not create joints and adapts to all types of surfaces,
- It is used on concrete, gas concrete, plaster, stucco and similar raw walls, old ironwashed, old emulsion-based interior and exterior painted surfaces.
- It is compatible with cement. It can also be used by mixing with cement and diluting it.

PRODUCT FEATURES

It penetrates the surface very well. It prepares a solid base and bonds the final coat of paint to the surface, reduces paint consumption, and reduces the water absorbency of plasters. It is also a primer with very high adhesion performance in water-based waterproofing materials and wall putty applications.

APPLICATION

Before application, swollen, loose and unhealthy looking surfaces should be scraped, oil and dirt should be wiped clean. If salt continues to appear on the surface, application should not be done until the reasons for this are eliminated.

GLOBAL PRIMER is mixed thoroughly until it becomes homogeneous before use and diluted with 7 times the volume of water, thoroughly absorbed into the surface with a brush, spray or roller and applied in a single coat. The application of paint or insulation product should be started after the primer has dried for at least 4 hours.

PACKAGING AND CONSUMPTION

It is offered for sale in 50 kg plastic drums with liquid consistency.

- Depending on the application technique and the absorbency of the surface, a consumption of 0.100 kg - 0.200 kg/m² is recommended, so as not to form a film on the concrete surface.
 - It is produced in transparent color. It can be diluted with water.
 - Before application, the surface must be cleaned of dirt, rust and oil.
 - In order for the mixture to be homogeneous, the mortar must be mixed thoroughly with a mixer.
 - It varies depending on the application technique and the absorbency of the surface.
 - It is compatible with cement and can be applied as a grout by mixing with cement.
-

WARNINGS

- Wear protective glasses during the painting process.
- If the dye comes into contact with your eyes, rinse your eyes with plenty of water and consult a doctor immediately.
- Ensure ventilation of your environment during painting and drying.
- Keep the paint can closed and away from children.
- Protect the paint from frost and excessive heat.
- Do not pour the remaining paint into the sink or toilet.
- Clean your brush and roller with water after each application.
- Be sure to carry the paint can safely and store it upright.