

TECHNICAL DATA

CORUHEAT PAINT

PRODUCT DESCRIPTION

It is a high performance interior and exterior coating based on acrylic copolymer emulsion, with a matte appearance and low thermal conductivity thanks to special spheres that provide thermal insulation.



AREAS OF USE

It is an ideal coating that you can use safely on old painted surfaces that have been painted before and lost their color, and on interior and exterior wall surfaces covered with plaster, lime, briquette, ytong, chipboard, wood and similar building elements.

FEATURES

- Its color does not fade, crack, swell or flake.
- It is resistant to atmospheric conditions and pollution, sunlight, friction and impacts.
- It does not have an annoying odor during application.
- Provides energy savings.
- It also has water and sound insulation properties.
- Does not retain dirt and is easy to clean.
- It has a combustion delay feature due to its late ignition.

APPLICATION

The surfaces on which CORU-TERMAL PAINT Thermal Insulation Coating will be applied must be clean and dry, free from all kinds of dirt, oil, dust and old paint residues. Roughnesses on the surface must be cleaned by scraping. Cracks must be repaired with acrylic-based putty. During application, care must be taken to ensure that the surface and ambient temperature is between +5°C and +30°C. After the surface preparation is completed, CORUUNEX UNIVERSAL is applied and the primer is left to dry for 4 hours. CORU-TERMAL PAINT - Thermal Insulation Coating must be mixed thoroughly before use. At least 3 coats must be applied on the exterior with a roller or brush, 1 or 2 coats on the interior, and 4 hours must be waited between coats. It is recommended that each coat be applied perpendicular to the previous coat.

NOTE: Ready to use. Mix well before use.

Drying Time (20°C) Initial Drying Time: 30 minutes Second Coat Application: 2 hours Final Drying: 24 hours Paintable Area 1 - 1.5 mm thick; 1 litre covers 1 m² on the exterior and 1 litre covers 3.5 m² on the interior.

STORAGE, PACKAGING, CONSUMPTION

- 1 year in its original unopened packaging at room temperature. Packaging 15.00 lt.