



TECHNICAL
DATA

CORU TENNIS



PRODUCT DESCRIPTION

Coru Tennis Court Paint is an acrylic copolymer emulsion based, matte looking court paint with high resistance to UV rays.

AREAS OF USE

It is used on all types of concrete except tennis courts, stock warehouses open to traffic, entrances, corridors and concretes without absorbent surfaces.

FEATURES

- It has excellent covering ability.
- Its color does not fade, crack, swell or flake.
- It is resistant to atmospheric conditions and pollution, sunlight, friction and impacts.
- Thanks to its high spreading power on the surface, it is easy to apply and saves time and labor.
- It gives a matte appearance to surfaces with its carefully selected colors and high quality.
- It does not have an annoying odor during application.

APPLICATION

The surfaces on which Coru - Tennis Court Paint will be applied must be clean and dry, free from all kinds of dirt, oil, dust, and old paint residues. Surface roughness must be cleaned by scraping. Cracks must be repaired with acrylic-based putty. During application, care must be taken to ensure that the surface and ambient temperature is between +5°C and +30°C. In order to prevent fluctuations on large surfaces, the material must always be diluted with the same amount of water, mixed thoroughly, and applied to the surface without interruption. There must be no excessive wind or air current in the application environment. The first coat of paint is diluted one-to-one and applied to the surface as a primer, and Bianca Coru - Tennis Court Paint is applied after 6 hours.

Thinning (by volume) Dilute with water by 10% maximum. Drying Time (20°C) Initial Drying Time: 30 minutes. Second Coat Application: 2 hours. Final Drying: 24 hours. Paintable Area 1 litre can paint an area of 6- 8 m² in a single coat, depending on the application method and the surface.

STORAGE, PACKAGING, CONSUMPTION

- 1 year in its original unopened packaging at room temperature. Packaging 15.00 lt.