



TECHNICAL DATA

CORUNEX THISOAL PREMIER



PRODUCT DESCRIPTION

It is a single component, resin-solvent based high adherence primer.

AREAS OF USE

- It is applied to absorbent surfaces such as concrete, screed and plaster.
- It is used in places where polysulphide paste is used, especially in concrete joints, to ensure better adhesion of the concrete and paste.

SURFACE PREPARATION

- Surfaces must be clean and free from loose particles. Application should not be made on wet or frozen surfaces.
- Previously applied mastic residues on the joints must be completely cleaned, and broken and irregular joints must be repaired before application.

APPLICATION

- Both sides of the joints are taped to prevent primer contamination.
- THIOSEAL PREMIER is applied to both sides of the joint with a clean brush and the tapes are removed.
- Wait for the primer to dry completely.
- Joint depth is limited with PE-based wick or similar.
- Then, polysulphide based joint filler is applied.

STORAGE, PACKAGING, CONSUMPTION

- It should be stacked up to 2 layers in its original packaging.
 - It should be stored in a closed area.
 - Necessary precautions must be taken against water, humidity, frost and severe weather conditions.
 - It should be stored on a pallet and in a dry place between +10°C and +25°C.
 - Punctured, opened and burst buckets should be closed or used immediately.
 - If the specified storage conditions are observed, the storage life is 12 months.
 - Consumption is 0.150-0.200 kg/m². Packaging is 1 kg tin can.
-

SAFETY AND WARNINGS

- It is not suitable for use under pressurized water, on glass and glazed surfaces, underground where there is high hydrostatic pressure, or on paint.
- Freshly applied material should not be exposed to rain or frost for 24 hours.
- CORUPU LINE should not be applied in rainy and foggy weather below (+) 5°C. It should not be applied to wet and frozen surfaces.
- Pay attention to the safety signs and warnings on the packaging.
- The health and safety information specified in the Product Safety Data Sheet (MSDS) prepared by a certified technical team in accordance with international standards (EC Directive 2001/58/EC) regarding the product must be followed.
- Adequate ventilation should be provided in workshops, and open flames and high temperatures should be avoided.
- Stir well before application. Do not leave the lid of the package open.
- Avoid application in weather conditions where rain is expected or under rain.
- It should not be brought into contact with skin, eyes and mouth, and the application should be carried out by taking the necessary work safety precautions.
- Avoid applying at temperatures below (+) 5°C and above (+) 30°C, do not try to use frozen material by adding water to it.